

• TRUSTED QUALITY SINCE 1921 •

**RUST-OLEUM®  
SPECIALTY**

**SPECIALTY  
LACQUER SPRAYS**

**DESCRIPTION AND USES**

Rust-Oleum® Lacquer Sprays is a high luster coating that provide a smooth, durable, ultra-hard, gloss finish on wood, metal, and more. Lacquer sprays are ideal for furniture, lamps, picture frames, and more.

**PRODUCTS**

<b>SKU (12 ounces)</b>	<b>Description</b>
272076	Blanco Brillante
272119	Negro Brillante
272121	Transparente Brillante

**PAINTING CONDITIONS**

Use outdoors or in a well ventilated area. Use when temperature is between 10-32°C and humidity is below 65% to ensure proper drying. Do not apply to surfaces, when heated, exceed 93°C. avoid spraying in very windy and dusty conditions. Cover surrounding area to protect from spray mist.

**PRODUCT APPLICATION**

**SURFACE PREPARATION**

Remove all dirt, grease, oil, salt and chemical contaminants by washing the surface with a commercial detergent, or other suitable cleaning method. Rinse with fresh water and allow to thoroughly dry. Remove loose paint and rust with a wire brush or sandpaper. Lightly sand glossy surfaces.

Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. LEAD IS TOXIC.

**PRODUCT APPLICATION (cont.)**

**APPLICATION**

Shake can vigorously for one minute after the mixing ball begins to rattle. If mixing ball fails to rattle DO NOT STRIKE CAN. Contact Rust-Oleum. Hold can upright 25-35 cm from surface and spray in a steady back and forth motion, slightly overlapping each stroke. Keep the can the same distance from the surface. Keep the can in motion while spraying. Apply two or more light coats a few minutes apart to avoid drips and runs. **Do not use near open flame.**

**DRY & RECOAT**

Dry and recoat times are based on 21°C and 50% relative humidity. Allow more time at cooler temperatures. Dries to the touch in 20 minutes and is fully dry in 30 minutes. May recoat at any time.

**CLEAN-UP**

Clean valve immediately after use by turning can upside down and depressing spray button for 3-5 seconds. Clean up wet paint with xylene or mineral spirits. Properly discard empty container. Do not burn or place in home trash compactor.

**CLOGGING**

If the valve clogs, twist and pull off spray tip and rinse in a solvent such as mineral spirits. Do not insert any object into can valve opening.

**TECHNICAL DATA**

**LACQUER SPRAYS**

**PHYSICAL PROPERTIES**

Physical Properties		LACQUER SPRAYS
Resin Type		Acrylic Lacquer
Pigment Type		Proprietary
Solvents		Acetone, Methyl Ethyl Ketone, Toluene
MIR		1.40 Max
Fill Weight		12 ounces
Practical Coverage at Recommended DFT (assumes 15% material loss)		Approximately 0.63 m <sup>2</sup> /can
Dry Times at 21-27°C and 50% Relative Humidity	Touch	20minutes
	Fully Dry	30 minutes
	Recoat	Anytime
Dry Heat Resistance		93°C
Shelf Life		5 years
Flash Point		-104°C
Safety Information		For additional information, see MSDS.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.